

UNITED STATES
PATENT APPLICATION
of
OSCAR L. AVANT
BRUCE A. BRANDT
and
JAY D. FADELY
for
APPARATUS AND METHODS
FOR IDENTIFYING A MAILPIECE
HAVING AN IDENTIFICATION CODE

5 I. Related Applications

This application claims the benefit of U.S. Provisional Patent Application No. 60/152,194, filed August 31, 1999, which is herein incorporated by reference.

10 II. Background of the Invention

A. Field of the Invention

The present invention relates to apparatus and methods for identifying and processing mail. More particularly, the present invention relates to apparatus and methods for using an identification code on a mailpiece as a redundant source of identification for identifying and processing the mailpiece in a mail sorting system.

15 B. Description of the Related Art

Conventional systems for identifying and processing (e.g., sorting) mail require both human and mechanical operations. Human operations are initially required to load the mail from a mail delivery repository into a mechanical identification and processing system. Mechanical operations then attempt to identify the delivery address for each mailpiece and, if successful, to then process each mailpiece based on the delivery address. Processing a mailpiece can be, for example, sorting the mailpiece. If there is a failure to identify the delivery address of a mailpiece mechanically, human operators are required again to identify the delivery address. Likewise, if there is a failure to process the mailpiece based on the delivery address, human operators are also required again to process the mailpiece. Therefore, conventional systems for

identifying and processing mail are dependent upon human operators, if the mechanical systems are unable to identify or process a mailpiece.

To identify mail with the conventional systems, mail is loaded into a mechanical identification system, which automatically feeds each mailpiece into an optical character reader (OCR) machine. The OCR machine then attempts to "electronically read" the delivery address from the mailpiece in order to place the delivery address in a computer. If the OCR machine cannot read the delivery address (e.g., the ZIP code), the mechanical device rejects the mailpiece. The rejected mailpiece may then be fed into another mechanical device, which presents the mailpiece to a human operator, who "physically reads" the delivery address off the mailpiece and key punches the delivery address into a computer. Once the delivery address has been either electronically or physically read and placed into a computer, the computer prints the delivery address on the mailpiece, using a special code (e.g., a bar code, such as, a POSTNET code).

To process mail with the conventional systems, mail is loaded into a mechanical processing system, which automatically sorts each mailpiece by the destination address. The majority of conventional mechanical processing systems sort each mailpiece based on a special code, such as, a ZIP code or a bar code (i.e., a POSTNET code). These mechanical processing systems may contain an OCR machine, which can read and sort a mailpiece based on the ZIP code. These mechanical processing systems may also contain a Bar Code Sorter, which can read

5

10

15

20

and sort a mailpiece based on the POSTNET code. If the mechanical processing system cannot read either the ZIP code or the POSTNET code, the system rejects the mailpiece. The rejected mailpiece may then be processed by a human operator. The human operator may then determine why the mechanical processing system rejected the mailpiece, solve the problem (e.g., determine the ZIP code or reaffix the POSTNET code to the mailpiece), and then reload the mailpiece into the mechanical processing system for processing.

To improve upon these conventional systems for identifying and processing mail, the United States Postal Service developed an automated sorting system, described in U.S. Patent No. 4,992,649 (the '649 patent), which is herein incorporated by reference. One embodiment of the system disclosed in the '649 patent is a Remote Bar Code System (RBCS). The embodiment of the RBCS described in the '649 patent provides for the electronic sorting of mail using a bar code that is placed on the front of each mailpiece, known as the POSTNET code, and another bar code that is placed on the back of each mailpiece, known as the ITEM code.

In the RBCS, the POSTNET code corresponds to the delivery address for the mailpiece, and the ITEM code corresponds to the mailpiece itself (i.e., the ITEM code is a means to "identify" each particular mailpiece). The POSTNET code represents a copy of the ZIP code in bar code format, and the POSTNET code can be used to route a mailpiece, if the ZIP code cannot be read. The ITEM code represents a unique code in bar code format, and the ITEM code can be used to identify each particular

mailpiece, if the RBCS cannot otherwise identify the mailpiece. For example, in the RBCS, the ITEM code can be linked to an electronic image of the mailpiece taken at the time the mailpiece is marked with the ITEM code by the RBCS. So, if the RBCS cannot identify a mailpiece, the RBCS can recall the electronic image of the mailpiece, which contains a destination address, including the POSTNET code.

The identification and processing of mail in the RBCS is dependent upon the use of either the POSTNET code or the ITEM code. When each mailpiece is identified by the RBCS, the ITEM code is first stored temporarily until the mailpiece receives the POSTNET code and has been processed by the RBCS. If the POSTNET code becomes illegible during processing, the ITEM code may be used to obtain the POSTNET code. The ITEM code is used to store a copy of the POSTNET code in a short-term memory until the RBCS has processed the mailpiece based on the POSTNET code. However, once the mailpiece has been processed and sorted based on the POSTNET code, the RBCS can no longer access the ITEM code, because the RBCS cannot store the ITEM code locally or transmit the ITEM code to other RBCS sites.

As a result, a number of problems can arise if the POSTNET code cannot be read by the RBCS. For instance, the POSTNET code on a mailpiece might be illegible as soon as it is applied due to the color or pattern of the mailpiece. If so, the mailpiece may be fed into a letter mail labeling machine that applies a white label to cover the illegible POSTNET code, and then, the mailpiece may be again fed into the RBCS

system for identification (and printing of a new POSTNET code on the white label). Additionally, the POSTNET code might be legible when applied, but become illegible during subsequent processing of the mailpiece. Because the ITEM code is only stored until the completion of the initial processing, the RBCS cannot use the ITEM code to identify the POSTNET code during subsequent processing and sorting. Therefore, if the POSTNET code becomes illegible during subsequent processing, the mailpiece can no longer be sorted automatically by the RBCS. These problems with the RBCS result in severe disadvantages, including diminishing the efficiency of the systems for identifying and processing mail and requiring excessive human intervention.

As indicated above, there are a number of shortcomings incumbent with these conventional systems for identifying and processing mail. It is therefore desirable to overcome these shortcomings by developing apparatus and methods to identify and process mail when the ZIP code is illegible. It is also desirable to overcome these shortcomings by developing apparatus and methods to identify and process mail when the POSTNET code is illegible. It is further desirable to overcome these shortcomings by developing apparatus and methods to identify and process mail when the ITEM code is illegible. It is still further desirable to overcome these shortcomings by developing apparatus and methods to establish a redundant identification code, which may be globally used by a system for identifying and processing mail. It is additionally desirable to overcome these shortcomings by developing apparatus and methods to read an identification code by a system for identifying and processing mail. It is still additionally

5

10

15

20

desirable to overcome these shortcomings by developing apparatus and methods to identify and process mail where a redundant identification code is used with a global system for identifying and processing mail, where one or more the nodes of the system are connected via hardware or software.

5

10 **III. Summary of the Invention**

Apparatus and methods consistent with the present invention overcome the shortcomings of the conventional systems by using an identification code on the back of each mailpiece as a redundant source of identification for identifying and processing mail in a mail sorting system.

15 Apparatus and methods consistent with the present invention identify a mailpiece in a mailpiece sorting system using an identification code corresponding to an identification file. The mailpiece is marked with the identification code on the back of the mailpiece and the identification file corresponding to the identification code is created. The identification file may be accessed from a plurality of nodes on the mailpiece sorting system. The identification code is used to retrieve identification information from the corresponding identification file at any node on the mailpiece sorting system.

20 Additional objects and advantages of the invention will be set forth in part in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention will

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N.W.
WASHINGTON, DC 20005
202-408-4000

be realized and attained by means of the elements and combinations particularly pointed out in the appended claims.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention, as claimed.

5

IV. Brief Description of the Drawings

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate several embodiments of the invention and, together with the description, serve to explain the principles of the invention.

10
15
20

In the drawings:

Figure 1 illustrates a simplified overview of the initial components or steps in apparatus or methods for identifying and processing a mailpiece consistent with the present invention;

Figures 2A and 2B illustrate embodiments of a mailpiece, consistent with apparatus or methods for identifying and processing mail consistent with one embodiment of the present invention;

Figure 3 shows an embodiment of an ID Tag in greater detail, as shown in Figure 2B;

20

Figure 4A depicts a simplified overview of a mailpiece as it enters a Post Office in a Remote Bar Code System (RBCS);

Figure 4B depicts a simplified overview of a mailpiece as it enters a Post Office in an Identification Code Sorting (ICS) system;

Figure 5 shows one embodiment of a Remote Bar Code System (RBCS), as shown in Figure 2A and 4A;

5 Figure 6A shows one embodiment of an Identification Code Sorting (ICS) system, as shown in Figures 2A and 4B;

Figure 6B shows an alternative embodiment of an Identification Code Sorting (ICS) system, as shown in Figures 2A and 4B;

10 Figure 7 is a detailed view of one embodiment of the section of an ICS system in which a mailpiece image (including an ID Tag) is processed to determine a POSTNET code (or ZIP code) corresponding to the destination address of a mailpiece, as shown in Figure 6A;

Figure 8 is a block diagram of one embodiment of an Image Control Unit (ICU) in greater detail;

15 Figure 9 is a block diagram of one embodiment of a Remote Computer Reader (RCR) in greater detail;

Figure 10 is a block diagram of one embodiment of an Image Buffer in greater detail;

20 Figure 11 is a block diagram of one embodiment of a Keying Site in greater detail;

Figure 12 is a block diagram of one embodiment of a Primary Identification Code Server/Secondary Identification Code Server (PICS/SICS) system, as shown in Figures 6A and 6B;

5 Figure 13 is a block diagram of one embodiment of a Primary Identification Code Server (PICS), as shown in Figure 12;

10 Figure 14 shows one embodiment of how a PICS functions, as shown in Figure 13;

15 Figure 15 is a block diagram of one embodiment of a Secondary Identification Code Server (SICS), as shown in Figure 14;

20 Figure 15A is a diagram of one embodiment of a plurality of Primary Identification Code Servers operating in national mode;

25 Figure 15B illustrates one embodiment of a process by which the sharing of mailpiece identification files takes place in national mode, as shown in Figure 15A;

30 Figure 16 depicts one embodiment of a PICS/SICS system incorporating Common Sorter Software;

35 Figure 17 is a block diagram of one embodiment of a Bar Code Sorter (BCS) system using Common Sorter Software to connect to a PICS;

40 Figure 18 illustrates various embodiments of Bar Code Sorters using Common Sorter Software to connect to a PICS/SICS such as the BCS systems shown in Figure 17;

SEARCHED
INDEXED
SERIALIZED
FILED
15

Figures 19A-19C illustrate one embodiment for a process used by one embodiment of Common Sorter Software during the identification and processing of a mailpiece by any of the Bar Code Sorters (BCS), such as those shown in Figure 18;

5

Figure 20 is a block diagram of a Bar Code Sorter (BCS) consistent with one embodiment of the present invention, for example, as used by a RBCS, which includes, for example, an RBCS ID Tag Reader;

10
15
20

Figure 21 is a block diagram of a Bar Code Sorter (BCS) consistent with one embodiment of the present invention, for example, as used by an ICS system, which includes, for example, a Universal ID Tag Reader;

Figure 22 is a block diagram of one embodiment of a Universal ID Tag Reader (UIDTR);

Figure 23 illustrates one embodiment of a UIDTR in greater detail, as shown in Figure 22;

Figures 24A-24D illustrate the operation of one embodiment of a UIDTR while processing a mailpiece, according to one embodiment of the invention;

Figure 25 shows optional components of an embodiment of a UIDTR such as the UIDTR in Figure 22; and

Figure 26 shows still additional optional components of another embodiment of a UIDTR, such as the UIDTR in Figure 22.

20

V. Detailed Description

5 A. Introduction

Apparatus and methods consistent with the present invention provide for identifying and processing mail using an identification code on a mailpiece as a redundant source of identification information in a mail sorting system. In one embodiment, this information is stored in a temporary database and used for the identification and processing of mail in a Remote Bar Code System (RBCS). In this embodiment, the identification code enables the automation of mail sorting and other processing tasks, reducing costs and delays in mail delivery services. In another embodiment, the identification and processing of mail occurs in an Identification Code Sorting (ICS) system. In this embodiment, a long-term database allows for mail sorting and other processing tasks on a national or global level.

10 Reference will now be made in detail to various embodiments of the invention, examples of which are illustrated in the accompanying drawings. Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the appended claims.

15 B. Overview of a System for Identifying and Processing Mail

20 Figure 1 illustrates a simplified overview of the initial components or steps in apparatus or methods for identifying and processing a mailpiece consistent with the present invention. In Figure 1, a mailpiece 100 is delivered by a postal customer 102 to

LAW OFFICES

FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.P.
1300 I STREET, N.W.
WASHINGTON, DC 20005
202-408-4000

a Post Office 104. Mailpiece 100 can be, for example, a letter or a package that postal customer 102 wishes to send to a destination address. To do so, postal customer 102 marks mailpiece 100 with a destination address and delivers it to Post Office 104. Post Office 104 can be a United States Postal Service (USPS) Post Office, a USPS mailbox, or any other facility or location capable of receiving a mailpiece or other item for delivery to a destination address using a system for identifying and processing mail.

1. POSTNET Code

Figures 2A and 2B illustrate embodiments of a mailpiece, consistent with apparatus or methods for identifying and processing mail consistent with one embodiment of the present invention. As shown in Figure 2A, mailpiece 100 contains two sources of delivery information, a destination address 200 and a POSTNET code 202 corresponding to destination address 200. For example, POSTNET code 202 can correspond to the ZIP code portion of destination address 200. POSTNET code 202 can be placed on mailpiece 100 by postal customer 102 or by the USPS at a processing center, e.g., Post Office 104. In systems consistent with apparatus or methods for identifying and processing mail consistent with one embodiment of the present invention, POSTNET code 202 can be read and used to route mailpiece 100 to a delivery facility, such as a Post Office, corresponding to destination address 200 for the delivery information. Therefore, if destination address 200 is illegible, POSTNET code 202 provides an alternative source of delivery information.

2. Identification Tag (ID Tag)

As shown in Figure 2B, in one embodiment, mailpiece 100 includes an identification code 204, also known as an identification tag (ID Tag), which is unique to mailpiece 100. ID Tag 204 provides an alternative source of delivery information in one embodiment of systems using apparatus or methods for identifying and processing mail consistent with the present invention. ID Tag 204 is printed on the back of mailpiece 5 100 and represents a unique identification source for identifying mailpiece 100. ID Tag 204 may be printed on mailpiece 100 in fluorescent ink. As described below, in one embodiment of systems consistent with the present invention, ID Tag 204 is used as a redundant source of identification throughout all phases of a mail identification and processing system.

Figure 3 shows an embodiment of an ID Tag in greater detail, as shown in Figure 2B. In this embodiment of the present invention, ID Tag 204 is represented by ID Tag bar code 300. ID Tag bar code 300 can contain bars and spaces indicating various information about mailpiece 100, including class of mail 304, origin optical character reader (OCR) number 306, day of the month 308, time of day 310, and mailpiece 15 sequence number 312. Class of mail code 304 can be represented by a single bit, representing either a 0 or a 1 to indicate mail classification. Origin OCR number 306 can be a series of 14 bits representing a machine ID number between 1 and 3,999. Day of month code 308 can be a series of 7 bits representing a day of the month between 1 and 31. Time of day code 310 can be a series of 7 bits representing a time of day, measured in half hour increments, between 0 and 47. Mailpiece sequence 20 20

number 312 can be a series of 18 bits representing a mailpiece sequence order from 1 to 25,000. In addition, ID Tag bar code 300 representing ID Tag 204 also contains a start code (such as a start bit) and a stop code (such as a stop bit). In ID Tag bar code 300, start code 302 is represented by a single bit and stop code 314 is represented by two bits. In one embodiment of systems consistent with the present invention, the combination of information represented in ID Tag bar code 300 uniquely identifies mailpiece 100. However, ID Tag 204 may be represented by formats other than ID Tag bar code 300.

5 C. Overview of Code-Based Systems for Identification and Processing Mail

10 1. Overview of RBCS

Figure 4A depicts a simplified overview of a mailpiece as it enters a Post Office in a Remote Bar Code System (RBCS). As shown in Figure 4A, mailpiece 100 enters a RBCS 500 for identification and processing to a destination address. In RBCS 500, mailpiece 100 can be identified by POSTNET code 202, which represents the ZIP code of the destination address, or ID Tag 204, which is stored temporarily within RBCS 500 during the initial identification and processing, as an identification code. RBCS 500 actually applies both POSTNET code 202 and ID Tag 204 to mailpiece 100. RBCS 500 first marks mailpiece 100 with ID Tag 204, and then RBCS 500 marks mailpiece 100 with POSTNET code 202. Then, after mailpiece 100 has been marked with POSTNET code 202 by RBCS 500, mailpiece 100 is then sorted in RBCS 500 based on POSTNET code 202, provided POSTNET code 202 is legible.

20
15
10
5
LAW OFFICES
FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

In RBCS 500, if POSTNET code 202 is not legible, RBCS 500 may use a special machine or a manual process to identify and process mailpiece 100 to a destination address. To use the special machine (described in detail herein), RBCS 500 may identify and process mailpiece 100 based on ID Tag 204. If ID Tag 204 is legible to this special machine, RBCS 500 can obtain POSTNET code 202 from a temporary database and thereby identify and continue to process mailpiece 100 to the destination address. Specifically, if this occurs, RBCS 500 reapplys POSTNET code 202 to mailpiece 100 and then again attempts to identify and process mailpiece 100 to the destination address. Notably, once mailpiece 100 leaves RBCS 500, ID Tag 204 is no longer stored within RBCS 500. Therefore, once mailpiece 100 has been marked with POSTNET code 202 (and has been verified by RBCS 500), ID Tag 204 can no longer be used to identify mailpiece 100.

2. Overview of ICS

Figure 4B depicts a simplified overview of a mailpiece as it enters a Post Office in an Identification Code Sorting (ICS) system. As shown in Figure 4B, mailpiece 100 enters an ICS system 600 for identification and processing to a destination address, like mailpiece 100 enters RBCS 500. In addition, in ICS system 600, mailpiece 100 can be identified by POSTNET code 202 and ID Tag 204, and ICS system 600 applies both POSTNET code 202 and ID Tag 204 to mailpiece 100. And, mailpiece 100 is also sorted by ICS system 600 based on POSTNET code 202, once ICS system 600 has marked mailpiece 100 with POSTNET code 202. However, in contrast to RBCS 500, ID

Tag 204 can be used in ICS system 600 at any time during the processing of mailpiece 100 from Post Office 104 to the destination address.

Consistent with one embodiment of the present invention, ICS system 600 utilizes computer hardware and software to maintain a long-term database for a plurality of ID Tags 204. In ICS system 600, if POSTNET code 202 becomes illegible, ID Tag 204 provides a source by which mailpiece 100 can be automatically identified and processed in ICS system 600 throughout the entire mail identification and processing system, whereby ICS system 600 references a long-term database stored within ICS system 600. In addition, ICS system 600 also enables many advanced processing capabilities based on ID Tag 204, including, for example, redundant ZIP code confirmation.

3. Detailed Description of RBCS

Figure 5 shows one embodiment of a Remote Bar Code System (RBCS), as shown in Figure 2A and 4A. When mailpiece 100 with destination address 200 enters Post Office 104 using RBCS 500, as shown in Figures 2A and 4A, processing begins at an Input Subsystem (ISS) 502. A piece of equipment at ISS 502, such as a MultiLine Optical Character Reader Input Subsystem, sprays (i.e., prints) ID Tag 204 onto the back of mailpiece 100 using, for example, fluorescent ink. ISS 502 also takes an image of mailpiece 100 (e.g., a digital image) and attempts to resolve the ZIP code portion of destination address 200, that is, ISS 502 attempts to determine POSTNET code 202 in sufficient detail to enable delivery of mailpiece 100 to destination address 200.

Sufficient detail may be, for example, a ZIP code with 5, 9, or 11 digits. If ISS 502 successfully resolves the ZIP code portion of destination address 200, ISS 502 then also sprays POSTNET code 202 corresponding to destination address 200 onto the front of mailpiece 100, for example, using nonfluorescent ink. Once RBCS 500 has affixed ID Tag 204 and POSTNET code 202 to mailpiece 100, ISS 502 then sends the POSTNET code information from POSTNET code 202 and the ID Tag information from ID Tag 204 to Image Control Unit (ICU) 508, where the POSTNET code information from POSTNET code 202 and the ID Tag information from ID Tag 204 is stored in Decision Storage Unit (DSU) 514.

If ISS 502 can resolve the ZIP code from destination address 200, and obtain POSTNET code 202 on mailpiece 100, ISS 502 then verifies POSTNET code 202 to confirm that POSTNET code 202 is legible. POSTNET code 202 may not be legible and may result in a verify error, if, for instance, mailpiece 100 is a color other than white or has a pattern that obscures POSTNET code 202. If ISS 502 cannot verify POSTNET code 202, mailpiece 100 is sent to an Output Subsystem 504 and marked for processing by a Letter Mail Labeling Machine (LMLM) 506. At LMLM 506, a white label is applied over the illegible POSTNET code, and mailpiece 100 is manually fed into OSS 504. The white label creates a clear area on mailpiece 100, and RBCS 500 then reapplies POSTNET code 202 onto the white label on mailpiece 100. OSS 504 then verifies POSTNET code 202 to confirm that POSTNET code 202 is legible. Once POSTNET code 202 is verified, ID Tag 204 has no further use.

If ISS 502 cannot resolve the ZIP code from destination address 200, then the mailpiece image, including ID Tag 204, is sent from ISS 502 to an Image Control Unit (ICU) 508. ICU 508 receives delivery address data from a Central Database 510 and forwards the data along with the mailpiece image, including ID Tag 204, to a Remote Computer Reader (RCR) 512. This delivery address data may include ZIP code data, POSTNET data, or temporary ID Tag files, as described in more detail herein. RCR 512 first attempts to use the data from the central database to automatically resolve the ZIP code corresponding to mailpiece 100. For example, RCR 512 uses ID Tag 204 to determine if there is a temporary file on mailpiece 100 in RBCS 500, which contains the ZIP code data. If RCR 512 is successful, it returns the ZIP code data to ICU 508, where the data is stored in a Decision Storage Unit (DSU) 514. If RCR 512 does not successfully resolve the ZIP code corresponding to mailpiece 100, the mailpiece image, including ID Tag 204, is sent from ICU 508 to a Keying Site 516, where a human operator views the mailpiece image and keys in the ZIP code data, which is returned to ICU 508 and stored in DSU 514. Therefore, in RBCS 500, regardless whether RCR 512 or Keying Site 516 resolves the ZIP code data, the ZIP code data, in the form of POSTNET code 202, is linked to ID Tag 204. All of this information, which is identified by ID Tag 204, is temporarily stored in DSU 514.

If ISS 502 cannot resolve the ZIP code from destination address 200, and while the mailpiece image is processed by ICU 508, mailpiece 100 is routed from ISS 502 to an Output Subsystem (OSS) 504. A Bar Code Sorter at OSS 504 reads ID Tag 204

from mailpiece 100 and transmits a lookup request to DSU 514. Once the ZIP code has been resolved for mailpiece 100, DSU 514 then retrieves and returns the ZIP code corresponding to ID Tag 204 to OSS 504, and OSS 504 then applies POSTNET code 202 to mailpiece 100, if necessary. OSS 504 then verifies POSTNET code 202 to confirm that POSTNET code 202 is legible. If OSS 504 cannot verify POSTNET code 202, mailpiece 100 is sent to LMLM 506 for manual processing as described above. OSS 504 then re-sprays and verifies POSTNET code 202 to confirm that POSTNET code 202 is legible. Once POSTNET code 202 is verified, ID Tag 204 has no further use and is no longer stored in RBCS 500.

After mailpiece 100 is processed by ISS 502 and OSS 504, initial mail processing of mailpiece 100 by RBCS 500 is complete at Post Office 104. If destination address 200 of mailpiece 100 indicates that mailpiece 100 is local mail, then RBCS 500 directs mailpiece 100 to mail carriers 518. However, if destination address 200 indicates that mailpiece 100 is not local mail, then RBCS 500 dispatches mailpiece 100 via one or more modes of transportation 520 to remote delivery sites 522.

4. Detailed Description of ICS

Figure 6A shows one embodiment of an Identification Code Sorting (ICS) system, as shown in Figures 2A and 4B. When mailpiece 100 enters Post Office 104 using ICS system 600, as shown in Figures 2A and 4B, processing begins at an ISS 602. A piece of equipment at ISS 602, such as a MultiLine Optical Character Reader Input Subsystem, sprays ID Tag 204 onto the back of mailpiece 100, for example, using

5

fluorescent ink. ISS 602 also takes an image (e.g., a digital image) of mailpiece 100 and attempts to resolve the ZIP code portion of destination address 200. If ISS 602 successfully resolves the ZIP code portion of destination address 200, ISS 602 then sprays POSTNET code 202 corresponding to destination address 200 onto the front of mailpiece 100, for example, using nonfluorescent ink. Once ICS system 600 has affixed ID Tag 204 and POSTNET code 202 to mailpiece 100, ISS 602 then sends the POSTNET code information from POSTNET code 202 and ID Tag information from ID Tag 204 to ICU 608, where the POSTNET code information from POSTNET code 202 and the ID Tag information from ID Tag 204 is stored in DSU 614 and ICS Buffer 616.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375

5

If ISS 602 cannot verify POSTNET code 202, ISS 602 may attempt to resolve the ZIP code from destination address 200 on mailpiece 100. If ISS 602 cannot resolve the ZIP code from destination address 200, then the mailpiece image, including ID Tag 204, is sent from ISS 602 to an Image Control Unit (ICU) 608. ICU 608 receives delivery address data from a Central Database 610 and forwards the data along with the mailpiece image, including ID Tag 204, to a Remote Computer Reader (RCR) 612. This delivery address data may include ZIP code data, POSTNET data, and/or ID Tag files, as described in more detail herein. RCR 612 first attempts to use the data from the central database to automatically resolve the ZIP code corresponding to mailpiece 100. For example, RCR 612 uses ID Tag 204 to determine if there is a file on mailpiece 100 in ICS system 600, which contains the ZIP code data. There should be a file for each mailpiece 100, so there should be a file in ICS system 600, which allows the ZIP code for mailpiece 100 to be resolved automatically by ICS system 600 without any human intervention. If RCR 612 is successful, it returns the ZIP code data to ICU 608, where the data is stored in a Decision Storage Unit (DSU) 614 and an ICS Buffer 616. If RCR 612 does not successfully resolve the ZIP code corresponding to mailpiece 100, then mailpiece 100 is processed as in RBCS 500, as described above. Also, if RCR 612 is not successful, ICS system 600 may use an Image Buffer 618 for priority designation, as described in more detail herein.

20

If ISS 602 cannot resolve the ZIP code from destination address 200, and while the mailpiece image is processed by ICU 608, mailpiece 100 is routed from ISS 602 to

5

OSS 604. A Bar Code Sorter at OSS 604 reads ID Tag 204 from mailpiece 100 and transmits a lookup request to DSU 614. Once the ZIP code has been resolved for mailpiece 100, DSU 614 then retrieves and returns the ZIP code corresponding to ID Tag 204 to OSS 604, and OSS 604 then applies POSTNET code 202 to mailpiece 100, if necessary. OSS 604 then verifies POSTNET code 202 to confirm that POSTNET code 202 is legible. However, in contrast to RBCS 500, even if OSS 604 cannot verify POSTNET code 202, mailpiece 100 can still be identified and processed in ICS system 600, if OSS 604 determines that mailpiece 100 is bound for an ICS-enabled destination. In this scenario, ICS system 600 simply uses ID Tag 204 as the identification code (instead of POSTNET code 202).

15

20

Therefore, in contrast to RBCS 500, ICS system 600 provides for the long-term storage of ID Tags 204 and corresponding POSTNET codes 202, which allows for the automation of tasks previously required to be performed by human operators. In addition, ICS system 600 provides for the sharing of this information throughout all phases of the identification and processing of mailpiece 100. This capability is made possible by Primary Identification Code Server/Secondary Identification Code Server (PICS/SICS) system 622. As described below, PICS/SICS system 622 enables downstream mailpiece identification and processing based on ID Tag 204, even if POSTNET code 202 becomes illegible. As in RBCS 500, after mailpiece 100 is processed by ISS 602 and OSS 604 in ICS system 600, initial mail processing is complete. Thereafter, mailpiece 100 is processed as in RBCS 500, a described above.

5

Figure 6B shows an alternative embodiment of an Identification Code Sorting (ICS) system, as shown in Figures 2A and 4B. In this embodiment, if RCR 612 does not successfully resolve the ZIP code corresponding to mailpiece 100, the mailpiece image is not stored in an image buffer (e.g., Image Buffer 618 in Figure 6A). Instead, RCR 612 sends the mailpiece image to ICU 608 indicating that the ZIP code has not been resolved, and ICU 608 transmits the mailpiece image to Keying Site 620. At Keying Site 620, processing occurs as described above with reference to Figure 6A.

a. Overview of Processing for Mailpiece Image

Figure 7 is a detailed view of one embodiment of the section of an ICS system in which a mailpiece image (including an ID Tag) is processed to determine a POSTNET code (or ZIP code) corresponding to the destination address of a mailpiece, as shown in Figure 6A. The mailpiece image (along with ID Tag 204), taken at ISS 602, is passed from ISS 602 to ICU 608 for processing. From ICU 608, the mailpiece image (and ID Tag 204) is passed to RCR 612. Also, Central Database 610 (e.g., a USPS master address database) passes data (e.g., POSTNET data and/or ZIP code data) via ICU 608 to RCR 612. RCR 612 processes the mailpiece image to resolve ZIP code data using the data received from Central Database 610. Generally, RCR 612 is able to resolve ZIP code data based on a file contained within Central Database 610—the file is identified by ID Tag 204. In effect, ID Tag 204 is used to match the mailpiece image to a file in Central Database 610. In ICS system 600, in contrast to RBCS 500, ID Tag

204 may be used to match the proper file in Central Database 610 throughout the identification and processing system.

Nonetheless, if RCR 612 fails, then the mailpiece image (and ID Tag 204) is stored in Image Buffer 618 in one embodiment, as shown in Figure 6A, which may include a priority designation, and is then sent to Keying Site 620, where it is processed according to the priority designation (if any). In an alternative embodiment without Image Buffer 618, as shown in Figure 6B, if RCR 612 does not resolve the ZIP code corresponding to mailpiece 100, RCR 612 sends the mailpiece image (and ID Tag 204) to ICU 608 indicating that the ZIP code has not been resolved, and ICU 608 then transmits this data to Keying Site 620.

During the subsequent processing in ICS system 600, when a ZIP code for the mailpiece image is resolved, either by RCR 612 or Keying Site 620, the ZIP code data is returned to ICU 608. ICU 608 then uses the ZIP code data to resolve the ZIP code for mailpiece 100. To do this, DSU 614 in ICU 608 sends the ZIP code data to OSS 604. ICU 608 also saves the ZIP code data in a storage system. ICU 608 informs Central Database 610 of the ZIP code data, which is mapped to ID Tag 204, which maintains a long-term storage capability. ICU 608 may also retain a local copy of the ZIP code data, which is mapped to ID Tag 204, at Image Buffer 618. As a result, ICS system 600 retains the ability to identify and process mailpiece 100 automatically throughout the delivery stages in a mail sorting system.

20 b. Detailed Description of Processing for Mailpiece Image

Figure 8 is a block diagram of one embodiment of an Image Control Unit (ICU) in greater detail. ICU 608 directs the processing of a mailpiece image corresponding to a mailpiece 100 in ICS system 600 to resolve a POSTNET code 202 (or ZIP code data), using ID Tag 204. ICU 608 receives from ISS 602 and stores the mailpiece image and ID Tag 204. ICU 608 also receives data, such as a master reference table, from Central Database 610. Central Database 610 can be, for example, a USPS master address database or a USPS address change service database. Central Database 610 can also contain identification files corresponding to a plurality of ID Tags 204. ICU 608 passes the mailpiece image (including ID Tag 204, not shown) and the master reference table to RCR 612.

Processing by RCR 612 is described below, with reference to Figure 9. If RCR 612 resolves the identification information, such as, POSTNET code 202 (or ZIP code data) corresponding to the mailpiece image, RCR 612 passes POSTNET code 202 to ICU 608, and POSTNET code 202 is stored along with ID Tag 204 in both DSU 614 and ICS Buffer 616. If RCR 612 does not resolve the identification information, such as, POSTNET code 202, then RCR 612 passes the mailpiece image and ID Tag 204 to Image Buffer 618. Processing by Image Buffer 618 is described below, with reference to Figure 10. At a particular time, such as, for example, the end of a mail sort run or the end of the day, Image Buffer 618 passes the mailpiece image (and ID Tag 204, not shown) to ICU 608, which passes the mailpiece image to Keying Site 620. Processing by Keying Site 620 is described below, with reference to Figure 11. Keying Site 620

returns an identification file, including POSTNET code 202, to ICU 608, where it is stored with ID Tag 204 in both DSU 614 and ICS Buffer 616. DSU 614 supplies identification information, such as ID Tag 204 and POSTNET code 202 for mailpiece 100, to OSS 604 during initial mail processing. ICS Buffer 616 retains a copy of this identification information locally for ICS system 600. A copy of ICS Buffer 616 may be sent to Central Database 610 for long-term storage.

Figure 9 is a block diagram of one embodiment of a Remote Computer Reader (RCR) in greater detail. RCR 612 receives the mailpiece image (including ID Tag 204, not shown) and the master reference table from ICU 608, as described above with reference to Figure 8. RCR 612 first attempts to compare the mailpiece image to data in the master reference table to resolve a POSTNET code for the mailpiece (i.e., mailpiece 100) corresponding to the mailpiece image. In doing so, RCR 612 uses ID Tag 204 to determine if there is a file on mailpiece 100, which contains identification information, such as, POSTNET code 202, for mailpiece 100. If RCR 612 succeeds, then RCR 612 sends POSTNET code 202 to ICU 608. If RCR 612 does not resolve the identification information, then, in one embodiment, RCR 612 assigns a priority designation to the mailpiece image and passes the mailpiece image (including ID Tag 204, not shown) and the priority designation to Image Buffer 618. Processing by Image Buffer 618 is described below, with reference to Figure 10. In an alternative embodiment (not shown), if RCR 612 does not resolve the POSTNET code, RCR 612 can send the mailpiece image or data indicating that the identification information has

not been resolved back to ICU 608. Processing by ICU 608 is described above, with reference to Figure 8.

Figure 10 is a block diagram of one embodiment of an Image Buffer in greater detail. Image Buffer 618 receives a Buffer File 1002 containing a mailpiece image (including ID Tag 204, not shown) and a priority designation from RCR 612. Image Buffer 618 stores Buffer File 1002. Upon the expiration of a condition (not shown), such as the end of a sort run or the end of the day, or upon receipt of a prompt from (as shown in Figure 10), for example, RCR 612, Image Buffer 618 sends Buffer File 1002 to ICU 608 for processing. Image Buffer 618 may also retain a copy of the identification information corresponding to a plurality of mailpieces 100 (i.e., a copy of a plurality of Buffer Files 1002). Alternatively, in certain other embodiments of ICS system 600, Image Buffer 618 is not implemented.

Figure 11 is a block diagram of one embodiment of a Keying Site in greater detail. In this embodiment, Keying Site 620 receives a Buffer File 1002 from ICU 608 that contains a mailpiece image (including ID Tag 204, not shown) and a corresponding priority designation, which is forwarded to a human operator for manual processing according to the priority designation. As shown in Figure 11, the mailpiece image from Buffer File 1002 is presented to an operator at a keying station 1102. The operator views the mailpiece image and keys the identification information into a computer at Keying Site 620, such as the ZIP code information for the POSTNET code corresponding to the mailpiece image. Keying Site 620 then returns the identification

information to ICU 608 as an identification file. It is to be understood that a priority designation is not necessary. Alternatively, Keying Site 620 could process mailpiece images on a first-received, first-processed basis, if priority designations are not used.

5

D. Primary Identification Code Server/Secondary Identification Code Server (PICS/SICS) System

Figure 12 is a block diagram of one embodiment of a Primary Identification Code Server/Secondary Identification Code Server (PICS/SICS) system, as shown in Figures 6A and 6B. As described above in Figures 6A and 6B, ICU 608 maintains ICS Buffer 616, which stores ID Tags and corresponding POSTNET codes for mailpieces. ICU 608 may share this information with PICS/SICS system 622. As shown in Figure 12, ICU 608 shares identification information with a Primary Identification Code Server (PICS) 1200 via a telecommunications connection 1202. PICS 1200 in turn shares the identification information with a Secondary Identification Code Server (SICS) 1204 via a telecommunications connection 1206.

15

As shown in Figure 12, PICS 1200 can also communicate with a Value Added Service System 1208 via telecommunications link 1210. Value Added Service System 1208 can be, for example, a system to track and report the performance of PICS/SICS system 622. Telecommunications connections 1202, 1206, and 1210 can be, for example, an Internet connection, a telephone line with a modem, a local area network (LAN), or a wide area network (WAN). In systems consistent with the present invention, PICS 1200 can communicate with multiple SICS to share a plurality of identification

5

information about a plurality of mailpieces. As also shown in Figure 12, PICS 1200 communicates with Bar Code Sorters (BCS) 1212, 1214, and 1216. SICS 1204 communicates with BCS 1218 and 1220. Of course, each PICS and SICS can interface with any number of BCS consistent with the present invention. The communication with Bar Code Sorters is described in further detail below, with reference to Figures 14 and 15.

10
15
20

Additionally, as shown in Figure 12, PICS system 1230, which contains PICS 1200 and BCS 1212, 1214, and 1216, is in the same physical location, such as, for example, a USPS Mail Processing & Distribution Center. In one implementation, a dedicated ICS local area network connects BCS 1212, 1214, and 1216 to PICS 1200. SICS system 1240, which contains SICS 1204 and BCS 1218 and 1220, is in a different physical location, such as, for example, a USPS Associate Office. In one implementation, a dedicated ICS local area network connects BCS 1218 and 1220 to SICS 1204. Other configurations of PICS system 1230 and/or SICS system 1240 are possible.

20

Figure 13 is a block diagram of one embodiment of a Primary Identification Code Server (PICS), as shown in Figure 12. As described above, PICS 1200 communicates with ICU 608 via telecommunications connection 1202. In one implementation, PICS 1200 maintains a Local.Sat file 1306 that includes all of the geographic areas, i.e., ZIP code zones, served by PICS 1200. PICS 1200 also includes a Mode Indicator 1308 that can be set to either local or national mode. In local mode, PICS 1200

communicates with one or more Bar Code Sorters (BCS) 1302, one or more Secondary Identification Code Servers (SICS) 1304, and one or more PICS. In national mode, PICS 1200 may additionally communicate with PICS 1200 via one or more Electronic Post Offices (EPOs) (not shown). National mode is described below, with reference to Figures 15A and 15B.

As shown in the depicted implementation in Figure 13, to identify information processed between ICU 608 and PICS 1200, PICS 1200 maintains a Lookup Table 1310. Identification files, or ID files, containing ID Tag and POSTNET data, are stored in the identification files in Lookup Table 1310. To serve one or more SICS 1304, PICS 1200 includes a SICS_ZIP Data File Generator 1312 and a SICS Service Area Table Database 1314. SICS_ZIP Data File Generator 1312 is used by PICS 1200 to create a SICS_ZIP Data File (not shown here, but see below) for each SICS connected to PICS 1200 by matching identification files from Lookup Table 1310 to the service area of each SICS. The service area of each SICS connected to PICS 1200, i.e., the geographic area served by each SICS, is stored in a SICS Service Area Table in SICS Service Area Table Database 1314.

Figure 14 shows one embodiment of how a PICS functions, as shown in Figure 13. PICS 1200 receives an identification file, including ID Tag 204 and POSTNET code 202, from ICU 608 via telecommunications link 1202. PICS 1200 stores the identification file in Lookup Table 1310. As shown in Figure 14, each identification file 1420 contains an identification code (ID code) 1422, such as, for example, ID Tag 204,

and a postal code 1424, such as, for example, POSTNET code 202. In addition, identification file 1420 can include additional information, such as, for example, an image capture time or status bits indicating various aspects of the identification file.

5 PICS 1200 contains SICS_ZIP Data File Generator 1312. SICS_ZIP Data File Generator 1312 is used by PICS 1200 to create a SICS_ZIP Data File 1406 for each SICS connected to PICS 1200 by matching identification files 1420 from Lookup Table 1310 to the service area of each SICS from SICS Service Area Table Database 1314. PICS 1200 maintains SICS Service Area Table Database 1314, which includes a set of SICS Service Area Tables corresponding to each SICS served by PICS 1200. For example, SICS 1404 would have a corresponding SICS Service Area Table 1315 in SICS Service Area Table Database 1314.

10 In one implementation of ICS system 600, referring to Figure 14, PICS 1200 has two functions. A first function of PICS 1200 is to resolve mailpiece information for Bar Code Sorter (BCS) 1402. To do this, BCS 1402 reads an identification code 1410 from a mailpiece and sends the identification code (or ID code or ID Tag) to PICS 1200, such as, for example, via a dedicated ICS local area network (not shown). PICS 1200 looks up identification code 1410 in Lookup Table 1310, and returns identification information, i.e., the ZIP code or the POSTNET code, corresponding to identification code 1410 to BCS 1402.

15 To do so, PICS 1200 matches identification code 1410 with an identification code contained in an identification file, such as identification code 1422 in identification

5

file 1420. Because ICS system 600 had previously created identification file 1420 corresponding to a single mailpiece (using the unique identification code 1422), PICS 1200 can accurately obtain the identification information using identification file 1420, which matches identification code 1422 to identification code 1410. Thereby, PICS 1200 can also determine that postal code 1424 corresponds to identification code 1410. PICS 1200 then returns identification information 1430 to BCS 1402. In one embodiment, identification information 1430 is postal code 1424. In an alternative embodiment, identification information 1430 is identification code 1422. In another alternative embodiment, identification information 1430 is identification file 1420. In still another alternative embodiment, identification information 1430 can be an entirely different code.

10
15
20

LAW OFFICES
FINNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N.W.
WASHINGTON, DC 20005
202-408-4000

A second function of PICS 1200 is to share information with one or more SICS 1404. To do this, at predetermined intervals, PICS 1200 sends information to SICS 1404 via a telecommunications connection. These intervals can be based on time (e.g., every twenty minutes, every hour, etc.) or on another measurement (e.g., once 20,000 identification files are stored in Lookup Table 1310, etc.). PICS 1200 uses SICS_ZIP Data File Generator 1312 to create a SICS_ZIP Data File 1406. SICS_ZIP Data File 1406 contains the identification files from Lookup Table 1310 for a particular SICS 1404. SICS_ZIP Data File Generator 1312 uses the appropriate SICS Service Area Table 1315 corresponding to SICS 1404 to determine which identification files are included in SICS_ZIP Data File 1406. For example, in SICS Service Area Table

Database 1314, there is a SICS Service Area Table 1315 that identifies the service area for a particular SICS, e.g., the ZIP codes for the zones served by SICS 1404. Thus, using this information (for purposes of this example), SICS_ZIP Data File Generator 1312 collects all identification files (e.g., identification files 1407) with the ZIP codes from SICS Service Area Table 1315 and creates SICS_ZIP Data File 1406. At the predetermined interval (described above), PICS 1200 then sends SICS_ZIP Data File 1406 containing identification files 1407 to SICS 1404.

Figure 15 is a block diagram of one embodiment of a Secondary Identification Code Server (SICS), as shown in Figure 14. In Figure 15, SICS 1404 performs the same basic function as PICS 1200 with respect to Bar Code Sorters. SICS 1404 resolves mailpiece information for one or more Bar Code Sorters, e.g., Bar Code Sorter (BCS) 1502. To do this, SICS 1404 receives a SICS_ZIP Data File 1406 from PICS 1200. For example, SICS_ZIP Data File 1406 may include a collection of identification files 1407 corresponding to mailpieces destined for postal codes within the service area of SICS 1404. In one implementation, when BCS 1502 reads an identification code 1510 from a mailpiece, BCS 1502 sends identification code 1510 to SICS 1404, such as, for example, over a dedicated ICS local area network (not shown). SICS 1404 looks up identification code 1510 in SICS_ZIP Data File 1406 and returns identification information, e.g., the ZIP code or the POSTNET code, to BCS 1502 in the form of identification information 1520. Accordingly, in this implementation, BCS 1502 can use identification information 1520 to identify and process the mailpiece even if the ZIP

code or the POSTNET code is illegible. Thus, like PICS 1200, SICS 1404 can determine mailpiece information for a Bar Code Sorter 1502.

Figure 15A is a diagram of one embodiment of a plurality of Primary Identification Code Servers operating in national mode. As in local mode, in which a PICS shares mailpiece identification information with one or more SICS and one or more PICS (see Figure 13), in national mode, a PICS additionally shares mailpiece identification with other PICS via one or more Electronic Post Offices (EPOs). As shown in Figure 15A, a plurality of PICS 1505 are connected to a plurality of EPOs 1502. In one implementation, PICS 1510, PICS 1511, and PICS 1512 are connected to ICS Electronic Post Office West 1504, ICS Electronic Post Office Central 1506, and ICS Electronic Post Office East 1508 via a network (not shown). Any number of PICS can be connected to any number of EPOs. This national mode implementation allows for broad interoperability among an unlimited number of PICS and EPOs. For example, as shown in Figure 15A, PICS 1510 may receive identification files for all mailpieces processed by all PICS in an ICS system 600. By allowing PICS 1510 to communicate with one or more of EPOs 1504, 1506, and 1508, the identification files for mailpieces bound for areas served by PICS 1511 and PICS 1512 are also sent from PICS 1510 to PICS 1511 and PICS 1512. Therefore, national mode allows for complete interoperability among all the components of an ICS system 600.

Figure 15B illustrates one embodiment of a process by which the sharing of mailpiece identification files takes place in national mode, as shown in Figure 15A. As

shown in Figure 15B, in national mode, PICS 1510 collects identification files in Lookup Table 1512, as described above. PICS 1510 then determines which of the identification files in Lookup Table 1512 are served by other PICS/SICS systems using a Local.Sat file 1514, as described above. PICS 1510 maintains an EPO.Sat file 1513 to define what records are to be sent to other PICS via EPOs. In one embodiment, Local.Sat file 1514 can contain a list of all ZIP codes served by PICS 1510 (as well as any SICS connected to PICS 1510). In this embodiment, EPO.Sat file 1513 can be the inverse of Local.Sat file 1514. PICS 1510 can have a National Mode indicator 1511. In national mode, PICS 1510 periodically sends these identification files to a primary EPO 1520 via a network connection (not depicted). PICS 1510 also sends a copy of Local.Sat file 1514 to primary EPO 1520. Local.Sat file 1514 contains a list of all the ZIP codes served by PICS 1510. In one implementation, PICS 1510 may also have a secondary EPO for use in case primary EPO 1520 is unavailable or inoperative (not shown).

Once PICS 1510 has transferred the identification files to EPO 1520, EPO 1520 collects and stores the identification files in a Storage Buffer 1514. EPO 1520 also collects and stores any Local.Sat files 1514 in a plurality of Table Buffers 1516. Each PICS table 1518 in PICS Table Buffer 1516 is created using the Local.Sat files received from the plurality of PICS operating in national mode, such as, PICS 1510. For example, when EPO 1520 receives Local.Sat file 1514 from PICS 1510, EPO 1520 creates a PICS Table 1518 corresponding to PICS 1510. Thereafter, in an implementation based on ZIP codes, as EPO 1520 receives identification files from

other PICS, EPO 1520 stores the identification files matching the ZIP codes in PICS Table Buffer 1516 in the corresponding PICS Table for each respective PICS (e.g., if the ZIP code matches the ZIP codes in PICS Table 1518 corresponding to Local.Sat file 1514, the identification file is matched to PICS Table 1518). At predetermined intervals (similar to the predetermined intervals described above), EPO 1520 then sends a copy of each PICS Table in PICS Table Buffer 1516 to its corresponding PICS. For example, if EPO 1520 collects identification files corresponding to PICS 1530 into a PICS Table 1519, EPO 1520 may send PICS table 1519 to PICS 1530. Additionally, EPO 1520 may also send a copy of National.Sat file 1515 to PICS 1530. National.Sat file 1515 is a compilation of all Local.Sat files received by EPO 1520. National.Sat file 1518 can be used by EPO 1520 to monitor all areas services by ICS system 600. If a copy is transferred from EPO 1520 to PICS 1530, National.Sat file 1518 can also be used by PICS 1530 to monitor all areas that are served by ICS system 600.

E. Common Sorter Software

As described above, as shown in Figures 12 and 13, both PICS and SICS exchange information with Bar Code Sorters (BCS). For example, PICS 1200 in Figure 13 exchanges information with a plurality of BCS 1302, and a plurality of SICS 1304 exchange information with a plurality of BCS 1306. Throughout ICS system 600, different types of BCS are used to read identification information from a mailpiece and process the mailpiece through a PICS or a SICS. Accordingly, using the same example

from Figure 13, a common sorter software is needed to allow PICS 1200 and SICS 1304 to exchange information with BCS 1302 and BCS 1306, respectively.

Figure 16 depicts one embodiment of a PICS/SICS system incorporating Common Sorter Software. Common Sorter Software 1602 performs a number of tasks, including, for example, initiating a connection between a BCS and a PICS and/or SICS, transmitting information between the BCS and the PICS and/or SICS, and terminating the connection between the BCS and the PICS and/or SICS. In this way, PICS 1200 processes mailpiece information for BCS 1212, 1214, and 1216, using Common Sorter Software 1602. Additionally, SICS 1204 processes mailpiece information for BCS 1218 and 1220, using Common Sorter Software 1602. Regardless of the type of BCS, Common Sorter Software 1602 provides a common interface between the BCS and a PICS and/or SICS. Therefore, Common Sorter Software 1602 is infinitely compatible (with any BCS) and infinitely expandable (to any number of BCS devices). Notably, in one implementation, Common Sorter Software 1602 is software, but Common Sorter Software 1602 may also be hardware.

Figure 17 is a block diagram of one embodiment of a Bar Code Sorter (BCS) system using Common Sorter Software to connect to a PICS. BCS system 1700 includes BCS 1212 and Common Sorter Software 1602. Common Sorter Software 1602 provides an interface between BCS system 1700 and PICS 1710. Of course, one skilled in the art would understand that other BCS may be similarly configured or that

BCS 1212 may use Common Sorter Software 1602 to interface with a SICS rather than a PICS (i.e., PICS 1700).

Figure 18 illustrates various embodiments of Bar Code Sorters using Common Sorter Software to connect to a PICS/SICS such as the BCS systems shown in Figure 17. As illustrated in Figure 18, Common Sorter Software 1602 can be used with a Mail Processing Bar Code Sorter (MPBCS) 1802, a Downstream Bar Code Sorter (DBCS) 1804, a Carrier Sequence Bar Code Sorter (CSBCS) 1806, an Output Subsystem/Bar Code Sorter (OSS/BCS) 1808, or any other type of Bar Code Sorter.

Figures 19A-19C illustrate one embodiment for a process used by one embodiment of Common Sorter Software during the identification and processing of a mailpiece by any of the Bar Code Sorters (BCS), such as those shown in Figure 18. First, as shown in Figure 19A, after an operator 1900 has loaded the mailpieces into BCS 1212, operator 1900 enters a 'Start Run' command into BCS 1212. BCS 1212 then begins the process of attempting to identify and process the mailpieces. During this process, a connection with a PICS/SICS 1810 may become necessary. BCS 1212 uses Common Sorter Software 1602 to establish a connection with PICS/SICS 1810. As shown in Figure 19B, operator 1900 can constantly supervise the identification and processing of the mailpieces on BCS 1212 (i.e., throughout the "mail sort run"). During this period, BCS 1212 uses Common Sorter Software 1602 to communicate with PICS/SICS 1810 throughout the mail sort run. As shown in Figure 19C, once the mail sort run is complete, operator 1900 enters an 'End Run' command into BCS 1212, and

Common Sorter Software 1602 breaks the connection with PICS/SICS 1810 until the next mail sort run. One skilled in the art would be aware of alternative processes by which BCS 1212 could connect with PICS/SICS 1810 via Common Sorter Software 1602.

5

F. Universal ID Tag Reader

As described above, as shown in Figures 12 and 13, a Bar Code Sorter (BCS) is used by ICS system 600 to read information from a mailpiece and to identify and process the mailpiece according to the information. As also described above, ICS system 600 uses special codes for the identification and processing of mail, namely, the POSTNET code (on the front of the mailpiece) and the identification code (on the back of the mailpiece). To read the identification code off the back of the mailpiece, RBCS 500 and ICS system 600 include special apparatus and processes, such as an ID Tag Reader (in RBCS 500) and an Universal ID Tag Reader (in ICS system 600).

10
09
08
07
06
05
04
03
02
01
00
09
08
07
06
05
04
03
02
01
00
15
09
08
07
06
05
04
03
02
01
00
20
09
08
07
06
05
04
03
02
01
00

Figure 20 is a block diagram of a Bar Code Sorter (BCS) consistent with one embodiment of the present invention, for example, as used by a RBCS, which includes, for example, an RBCS ID Tag Reader. BCS 1212 includes a Bar Code Sorting System 2002, Common Sorter Software 1602, and a RBCS ID Tag Reader 2000. As described above, RBCS 500 makes only limited use of an identification code, because identification files are temporary and may only be used locally. For this reason, RBCS ID Tag Reader 2000 is generally used with a single type of BCS, namely, the OSS/BCS 1808, as shown in Figure 18.

Figure 21 is a block diagram of a Bar Code Sorter (BCS) consistent with one embodiment of the present invention, for example, as used by an ICS system, which includes, for example, a Universal ID Tag Reader. BCS 1212 in ICS system 600 includes Bar Code Sorting System 2002, Common Sorter Software 1602, and a Universal ID Tag Reader 2100. As described above, ICS system 600 makes widespread use of an identification code, and therefore, Universal ID Tag Reader 2100 has many applications. For example, Universal ID Tag Reader 2100 can be used on any type of BCS, including MPBCS 1802, DBCS 1804, CSBCS 1806, and OSS/BCS 1808, as shown in Figure 18.

Figure 22 is a block diagram of one embodiment of a Universal ID Tag Reader (UIDTR). UIDTR 2100 includes two main components: a Reader Head Assembly 2200 and a Reader Unit 2202 connected by a Fiber Optic Cable 2204. Notably, because Reader Head Assembly 2200 is separate from Reader Unit 2202, Reader Head Assembly 2200 may be placed in an assortment of different positions within ICS system 600, connected by Fiber Optic Cable 2204. In contrast to RBCS ID Tag Reader 2000, therefore, UIDTR 2100 has increased flexibility and usability in ICS system 600.

Figure 23 illustrates one embodiment of a UIDTR in greater detail, as shown in Figure 22. Reader Head Assembly 2200 includes an Infrared Receiver 2302 and a Lens 2304. Reader Unit 2202 includes a Reader Logic Unit 2306, a Light Source 2308, a Light Filter Unit 2310, a Signal Converter 2318, and a Port 2320. In this embodiment, Light Filter Unit 2310 includes a first Light Filter 2312, a second Light Filter 2314, and a

third Light Filter 2316. One skilled in the art would recognize that other embodiments may be used for the arrangement of light filters in Reader Unit 2202. Reader Head Assembly 2200 is connected to Reader Unit 2202 via Fiber Optic Bundle 2204.

Figures 24A-24D illustrate the operation of one embodiment of a UIDTR while processing a mailpiece, according to one embodiment of the invention. As shown in Figure 24A, mailpiece 100 includes an identification code, i.e., an ID code. When mailpiece 100 is placed before Universal ID Tag Reader 2100, a light barrier signal is generated at Infrared Receiver 2302. Infrared Receiver 2302 passes the light barrier signal to Reader Logic Unit 2306. The light barrier signal indicates that there is a mailpiece ready to be processed. As shown in Figure 24B, reader Logic Unit 2306 then supplies power to Light Source 2308. The light from Light Source 2308 travels over Fiber Optic Bundle 2204 and illuminates the ID code on the mailpiece. As shown in Figure 24C, lens 2304 then focuses the ID code onto Fiber Optic Bundle 2204. In one embodiment, Fiber Optic Bundle 2204 may divide the light into at least three bundles. One skilled in the art would recognize that other embodiments may be used, including less than three bundles. Each bundle is directed to a light filter in Light Filter Unit 2310. The first bundle is filtered through a First Light Filter 2312, the second bundle is filtered through a Second Light Filter 2314, and the third bundle is filtered through a Third Light Filter 2316. In this embodiment, the light filters (i.e., First Light Filter 2312, Second Light Filter 2314, and Third Light Filter 2316) respond to different frequencies of the fluorescent spectrum. The analog signals output by Light Filter Unit 2310 are then

converted into digital signals by Signal Converter 2318, e.g., an analog/digital converter. Finally, as shown in Figure 24D, the digital signal from Signal Converter 2318 is passed to Reader Logic Unit 2306, where the digital signal is converted into an ID code corresponding to the ID code on mailpiece 100. Reader Logic Unit 2306 passes the ID code to Port 2320, and the ID code is passed back to BCS 1212.

Figure 25 shows optional components of an embodiment of a UIDTR such as the UIDTR in Figure 22. As shown in Figure 25, an operator 2500 can operate Universal ID Tag Reader 2100 using one or more Light Emitting Diodes 2502 on Reader Head Assembly 2200 and one or more Light Emitting Diodes 2504 and Push Buttons 2506, located on Reader Unit 2202. Light Emitting Diodes 2502 and/or Light Emitting Diodes 2504 can display diagnostic information, such as 'System OK' or 'Power OK,' or function options, such as 'Reset,' to operator 2500. Operator 2500 can use Push Buttons 2506 to display diagnostic information, to select function options or to input other data.

Figure 26 shows still additional optional components of another embodiment of a UIDTR, such as the UIDTR in Figure 22. Port 2602 can support, for example, transistor transistor logic (TTL) and Port 2604 can support, for example, differential logic. These optional component ports may enable, for example, UIDTR 2100 to function with an expanded variety of Bar Code Sorters.

5

10

15

20

VI. Conclusion

As described above, therefore, it will be apparent to those skilled in the art that various modifications and variations can be made in the methods and apparatus of the present invention without departing from the spirit and scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention, provided they come within the scope of the appended claims and their equivalents. In this context, equivalents mean each and every implementation for carrying out the functions recited in the claims, even if not explicitly described herein.

6

100 *Journal of Health Politics, Policy and Law*